

Package: minesweeper (via r-universe)

August 30, 2024

Type Package

Title Play Minesweeper

Version 0.1.0

Description Play and record games of minesweeper using a graphics device that supports event handling. Replay recorded games and save GIF animations of them.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports grid

Suggests gifski

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Depends R (>= 2.10)

URL <https://github.com/hrryt/minesweeper>

BugReports <https://github.com/hrryt/minesweeper/issues>

Repository <https://hrryt.r-universe.dev>

RemoteUrl <https://github.com/hrryt/minesweeper>

RemoteRef HEAD

RemoteSha e17c77b176536fcba004167a230d3507194fead6

Contents

play_minesweeper	2
replay_minesweeper	3
save_minesweeper_gif	3

Index	5
--------------	----------

play_minesweeper *Start a Minesweeper Game*

Description

Play minesweeper interactively in the current graphics device.

Usage

```
play_minesweeper(  
  difficulty = c("expert", "intermediate", "beginner"),  
  nrow = NULL,  
  ncol = NULL,  
  mine_count = NULL,  
  mine_density = NULL  
)
```

Arguments

difficulty	establishes default dimensions and mine count
nrow, ncol	dimensions of the minesweeper board
mine_count	number of mines to sweep
mine_density	proportion of cells that conceal a mine

Details

Expert difficulty is 16x30 with 99 mines, intermediate 16x16 with 40 mines, and beginner 9x9 with 10 mines.

The current graphics device must support event handling (see `grDevices::getGraphicsEvent()`). If `onIdle` is not supported, the timer will only update on mouse events.

Value

Object of class "minesweeper_recording" to pass to `replay_minesweeper()` or `save_minesweeper_gif()`, invisibly.

Examples

```
dev.new(noRStudioGD = TRUE)  
recording <- play_minesweeper()  
dev.off()
```

replay_minesweeper	<i>Replay a Minesweeper Recording</i>
--------------------	---------------------------------------

Description

Replay a recorded game of minesweeper in the current graphics device.

Usage

```
replay_minesweeper(recording)
```

Arguments

recording object of class "minesweeper_recording" returned by [play_minesweeper\(\)](#)

Value

recording, invisibly.

Examples

```
dev.new(noRStudioGD = TRUE)
recording <- play_minesweeper()
replay_minesweeper(recording)
dev.off()
```

save_minesweeper_gif	<i>Save a Minesweeper Recording to GIF</i>
----------------------	--

Description

Save a recorded game of minesweeper to a GIF file.

Usage

```
save_minesweeper_gif(
  recording,
  gif_file = "animation.gif",
  width = 800,
  height = 600,
  delay = 1,
  loop = TRUE,
  progress = TRUE,
  ...
)
```

Arguments

recording	object of class "minesweeper_recording" returned by play_minesweeper()
gif_file	output gif file
width	gif width in pixels
height	gif height in pixel
delay	time to show each image in seconds
loop	if the gif should be repeated. Set to FALSE to only play once, or a number to indicate how many times to repeat after the first.
progress	print some verbose status output
...	other graphical parameters passed to png

Details

Reduce the delay for greater temporal resolution.

Value

The file path of the GIF file.

Examples

```
dev.new(noRStudioGD = TRUE)
recording <- play_minesweeper()
save_minesweeper_gif(recording)
dev.off()
```

Index

`grDevices::getGraphicsEvent()`, 2

`play_minesweeper`, 2

`play_minesweeper()`, 3, 4

`png`, 4

`replay_minesweeper`, 3

`replay_minesweeper()`, 2

`save_minesweeper_gif`, 3

`save_minesweeper_gif()`, 2